



Preparing Door

Checklist items:
 ✓ Marking the door.
 ✓ Drilling holes.
 ✓ Ensuring bolt is in retracted (unlocked) position.

1 Installing Latch & Strike Plate

60mm-- position
x4
default
70mm position
optional
Press
Pull

Bolt must be in retracted (unlocked) position. Note horizontal orientation of mechanism.

2 Installing Touchscreen Escutcheon

Inside of Door
Outside of Door
Bolt must be in retracted (unlocked) position. Note horizontal orientation of mechanism.

3 Installing Interior Mounting Plate

Loosen screw to remove cover
Choose correct length screw to suit door thickness
x2

FAILURE TO FOLLOW THESE INSTRUCTIONS COULD RESULT IN DAMAGE TO THE PRODUCT AND VOID THE FACTORY WARRANTY

An ASSA ABLOY Group brand P/N YRL- Program APAC ASSA ABLOY

4 Attaching the Cable Assembly

CABLE HOOK

5 Installing Interior Escutcheon

x3

Testing Operation-

⊗ 3
⊗ Bolt must be in retracted (unlocked) position before installing batteries.

6 Installing Batteries/Handing the Lock

"Welcome to Yale"
Lock automatically adjusts for correct handing.

7 Installing Optional Radio Module

Batteries must be removed prior to removing and / or inserting network module.

8 Installing Cover

Tighten screw to replace cover

Congratulations, you've installed the Yale Key Free Touchscreen Deadbolt!
Please Turn sheet over for Programming Instructions to customize your product.

